

# Mahindra Mould Board Plough

Mahindra MB plough is tractor-drawn conventional implement being widely used for primary tillage operations. It is helpful in hard soil conditions and in the soil where securing is a problem.

Mould Board Plough has special wear-resistant steel blades with bar points for the toughest ploughing jobs.



## KEY FEATURES

### **Shear Bolt Safety Protection**

Easily replaceable shear bolt device to avoid additional load such as stones & tree roots.

### **Working Width Adjustment**

Adjustable working width- 10", 12", 14" for different types of soil & moisture content.

### **Reliable Turnover & Infinite Angle Adjustment**

Hydraulic turnover device for precise, safe & quick turnover action. Independent LH & RH work angle can be adjusted as well.

### **Center Adjustment Setting**

Easy & independent adjustment of front furrow width & tractor pull line via center adjustment.

### **Underbody and Interbody clearance**

Large underbody & interbody clearance to avoid blockages even at close settings for furrows.

### **Mould Board**

Unique die-cut mould board to give smooth soil turnover & increased fuel efficiency.

## TECHNICAL SPECIFICATIONS

| Parameters                           | 2 Bottom MB plough  | 3 Bottom MB plough  | 4 Bottom MB plough  |
|--------------------------------------|---------------------|---------------------|---------------------|
| Furrow                               | 2                   | 3                   | 4                   |
| Complete width of Cut in (Inch / cm) | 24 / 61             | 36 / 91             | 48 / 122            |
| Mounting CAT                         | Cat II              | Cat II              | Cat II              |
| 3 Point Linkage Flat                 | 75 X 12T / 65 X 16T | 75 X 12T / 65 X 16T | 75 X 12T / 65 X 16T |
| Depth of Cut (Inch /cm)              | 8 to 12 / 20 to 30  | 8 to 12 / 20 to 30  | 8 to 12 / 20 to 30  |
| Beam thickness (mm)                  | 100 X 20            | 100 X 25            | 100 X 25            |
| Shear Bar Size (mm)                  | 40 X 25             | 40 X 25             | 40 X 25             |
| Material of Shear Point              | EN 8                | EN 8                | EN 8                |
| Total Weight (Kg)                    | 230                 | 320                 | 425                 |
| Suitable hp / kW Range               | 45 to 55 / 34 to 41 | 55 to 70 / 41 to 52 | 70 to 90 / 52 to 67 |

**Address**

Mahindra & Mahindra Ltd. Farm Equipment Sector,  
Farm Division AFS Headquarters, Mahindra Tower,  
1<sup>st</sup> Floor, Akurli Road, Kandivali (E), Mumbai-400101,  
India

**Dealer's / Distributor's stamp**