











TECHNICAL SPECIFICATIONS

ENGINE	
	M&M 805DI Turbocharged Four Cylinder, Four Stroke, Water Cooled Diesel Engine
POWER:	72 HP @ 2300 rpm
GROUND DRIVE	
Fully Hydrostatic Speed Range	0-9 Km/hr
CUTTING MECHANISM	
Cutter Bar Working Width	2.10 meter (7feet)
THRESHING MECHANISM	
Rotor Threshing & Separating Drum Dia	480mm
CLEANING MECHANISM	
Туре	Forced air cleaning fan
Sieve cleaning area	1.25 Sq.m
FUEL CONSUMPTION	7 ~ 8 ltr/hr*

Salient F	eatures ·	- Pro	Combine	7060	(TAF)
-----------	-----------	-------	---------	------	-------

- Rugged, reliable & More Powerful & fuel-efficient Mahindra 805DI Engine (72 HP @ 2300 rpm)
- Sturdy & low ratio reduction gear box along with low speed/high torque hydraulic motor-less wear tear-longer life
- Threshing TAF Type, Grain Loss is minimal.
- No Grain Breakage.

TRACK ASSY		
No. Off Grousers (each side)	60 (Bridgestone)	
Width Of Track	450mm	
Length Of Track On Ground	1730mm	
MAIN DIMENSIONS		
Overall Width	2620mm	
Overall Length	5740mm	
Overall Height	2940mm	
CAPACITIES		
Grain Tank	1.212 Cu meter (750 Kg)	
Fuel Tank	110 Ltr.	
WEIGHT		
Grain Tank Empty	4870Kgs.	
Grain Tank Full	5700 Kgs.	

- Additional Ladder provide at Grain tank & rear of Machine for ease of Serviceability.
- · Mobile charger provided.
- Overhead guard provided to prevent Electrocution from low lying electric cables in the field.
- Footrest provided above discharge tube
- New paddy special cutter bar for efficient cutting of sleeping crop
- Additional pentagon wheel provided in Reel drive for extra strength

Works: Swaraj Division,

Village Chappercheri, P.O. Landran,

District - Mohali (Punjab) Pin: 140307. Call: +918888200022 / +917744911119