


KEY FEATURES



Robust and Sturdy Multispeed Gearbox

Ensures its longer life even when it works in hard soils.



Right Geometry of Rotor Shaft and Mast

Helps to give better stability while working & Reduce the vibration.




Double Cone Mechanical Seal

Prevents dust or dirt from entering, ensuring longer life of seals and bearings.



Strong Mast

Absorbs vibrations, ensures smoother operations, and thereby contributes to breakdown free usage.



Mahindra BoroBladesTM

Made from specially sourced Boron steel, these high durability blades ensure low maintenance.



Superior Aesthetics

Excellent paint gloss retention & welding finish.

Parameters	1.6 m	1.8 m	2.1 m	2.3 m	2.5 m
Suitable Tractor (kW)	33 - 37	37 - 41	41-45	45-48	48-52
Suitable Tractor (hp)	45-50	50-55	55-60	60-65	65-70
Working Width, plate in to in (mm)	1636	1889	2142	2340	2647
Total Width (mm)	1801	2054	2307	2505	2812
Tilling Width, Blade out to out (mm)	1544	1797	2050	2249	2556
Total Length (mm)	951	951	951	1069	1020
Total Height (mm)	1149	1149	1149	1155	1149
Working Depth (mm)*	100-140	100-140	100-140	100-140	100-140
Number of Blades	36	42	48	54	60
Blade Compatibility	L/C	L/C	L/C	L/C	L/C
Primary Gear Box	Multi Speed				
Side Transmission	Gear Drive				
Weight, Without Propeller Shaft (kg)	438	480	506	570	610
Standard Speed Gears	17/21	17/21	17/21	17/21	17/21

^{*}Depth will differ, depending on soil conditions

Address

Mahindra & Mahindra Ltd. Farm Equipment Sector, Farm Division AFS Headquarters, Mahindra Tower, 1st Floor, Akurli Road, Kandivali (E), Mumbai-400101, India

Dealer's / Distributor's stamp

Technical specifications are subject to change due to continuous improvements on products.