

Mahindra Airotec Turbo 2000L

The Mahindra Airotec Turbo 2000 Sprayer distinguishes itself as a versatile and efficient agricultural implement crafted for a broad spectrum of applications in orchards and vineyards. Its exceptional maneuverability, defined by a low turning radius, allows for trouble-free navigation in restricted spaces. Moreover, the sprayer's adaptability is a notable attribute, courtesy of its innovative three-way adjustable tyre system, granting users the flexibility to customize track width, height, and tyre positioning to suit their individual requirements.



KEY FEATURES

- High air output with perfect air balancing at both side with lowest power consumption
- Stainless steel shell assembly
- Manual Controller: 5-mode controller & 2-way nozzles provide accurate delivery of chemicals
- Safety Devices: Innova rubber coupling & pressure relief valve
- Tank: HDPE - High Density Polyethylene
- Agitator: For proper agitation of chemical at the time of spraying
- Tyre Position Adjustment: Track width, height, tyre position forward & reverse
- Scrapper: For removing mud from tyre

TECHNICAL SPECIFICATIONS

Model	Airotec Turbo 2000L	
Length (mm)	3880	
Width (mm)	1670	
Height (mm)	1700	
Ground clearance from lowest position (axel tube stud) (mm)	305	
Machine Empty Weight (kg)	780	
Fan Size (mm)	712	
Diaphragm pump (LPM)	75	
Number of Nozzle	14	
OM kit (4 Handgun)	Yes	
Main Tank capacity (L)	2000	
Rinsing tank capacity (L)	145	
Handwash tank capacity (L)	20	
Air Velocity	m/s	38
	km/h	137
Vertical spray reach without high ambient wind (3-4 m/sec)	feet	24
	metre	8
Horizontal spray reach without high ambient wind on left & right side (3-4 m/sec)	feet	12
	metre	4

Address

Mahindra & Mahindra Ltd. Farm Equipment Sector,
Farm Division AFS Headquarters, Mahindra Tower,
1st Floor, Akurli Road, Kandivali (E), Mumbai-400101,
India

Dealer's / Distributor's stamp