

Mahindra Airotec Turbo 600L

The Mahindra Airotec Turbo 600L is a versatile agricultural sprayer designed for orchards and vineyards. It features an efficient air conveyor system for optimal air balance and low power consumption. The compact tank design and high-pressure jet ensure uniform chemical mixing. Adjustable track width, height, and tire positioning make it adaptable to various farming needs. Safety features, including rubber couplings and pressure relief valves, enhance its reliability, while hot-dip galvanized components ensure a long-lasting, rust-free performance.



KEY FEATURES

- High air output with perfect air balancing at both side with lowest power consumption
- 3 axis toe bar: Best for operations in low spacing vineyards
- Manual Controller: 5-mode controller & 2-way nozzles provide accurate delivery of chemicals
- Safety Devices: Innova rubber coupling & pressure relief valve
- Tank: HDPE - High Density Polyethylene
- Agitator: for proper agitation of chemical at the time of spraying
- Tyre position adjustment: Track width, height, tyre position forward & reverse
- Scraper: for removing mud from tyre

TECHNICAL SPECIFICATIONS

Model	Airotec Turbo 600L	
Length (mm)	2490	
Width (mm)	1140	
Height (mm)	1320	
Ground clearance from lowest position (axel tube stud) (mm)	230	
Machine Empty Weight (kg)	475	
Fan Size (mm)	616	
Diaphragm pump (LPM)	75	
Number of Nozzle	12	
OM kit (4 Handgun)	No	
Main Tank capacity (L)	600	
Rinsing tank capacity (L)	70	
Handwash tank capacity (L)	20	
Air Velocity	m/s	32
	km/h	115
Vertical spray reach without high ambient wind (3-4 m/sec)	feet	12
	metre	4
Horizontal spray reach without high ambient wind on left & right side (3-4 m/sec)	feet	6
	metre	2

Address

Mahindra & Mahindra Ltd. Farm Equipment Sector,
Farm Division AFS Headquarters, Mahindra Tower,
1st Floor, Akurli Road, Kandivali (E), Mumbai-400101,
India

Dealer's / Distributor's stamp