

Mahindra Airotec Turbo 1000L

The Mahindra Airotec Turbo 1000 Sprayer excels as a versatile and efficient agricultural implement engineered for a wide array of uses in orchards and vineyards. Its remarkable manoeuvrability, marked by a low turning radius, ensures effortless navigation through tight spaces. Additionally, the sprayer's adaptability is a prominent feature, courtesy of its innovative three-way adjustable tyre system, affording users the flexibility to customise track width, height, and tyre positioning to meet their specific requirements.



KEY FEATURES

- High air output with perfect air balancing at both side with lowest power consumption
- Stainless steel shell assembly
- Manual Controller: 5-mode controller & 2-way nozzles provide accurate delivery of chemicals
- Safety Devices: Innova rubber coupling & pressure relief valve
- Tank: HDPE - High Density Polyethylene
- Agitator: for proper agitation of chemical at the time of spraying
- Tyre position adjustment: Track width, height, tyre position forward & reverse
- Scrapper: for removing mud from tyre

TECHNICAL SPECIFICATIONS

Model	Airotec Turbo 1000L	
Length (mm)	3430	
Width (mm)	1480	
Height (mm)	1490	
Ground clearance from lowest position (axel tube stud) (mm)	280	
Machine Empty Weight (kg)	610	
Fan Size (mm)	712	
Diaphragm pump (LPM)	75	
Number of Nozzle	14	
OM kit (4 Handgun)	No	
Main Tank capacity (L)	1000	
Rinsing tank capacity (L)	75	
Handwash tank capacity (L)	20	
Air Velocity	m/s	38
	km/h	137
Vertical spray reach without high ambient wind (3-4 m/sec)	feet	18
	metre	6
Horizontal spray reach without high ambient wind on left & right side (3-4 m/sec)	feet	9
	metre	3

Address

Mahindra & Mahindra Ltd. Farm Equipment Sector,
Farm Division AFS Headquarters, Mahindra Tower,
1st Floor, Akurli Road, Kandivali (E), Mumbai-400101,
India

Dealer's / Distributor's stamp